

10 inch Anti-Glare Screen Protector

Part No. AM10AGS

SUITABLE FOR

AM1005D 10 inch tablet style car head unit. The anti-glare surface cuts glare and reflections for easier viewing in bright light. Check it matches your screen before you start.

BEFORE YOU START

Fit in a clean, dust-free spot, out of direct sun. Switch the head unit off and let the screen cool.


IN THE BOX

1x Screen Protector
1x Microfibre Cloth

1x Cleaning Wipe
1x Dust Absorber

3x Alignment Guide Stickers
1x Smoothing Squeegee


FITTING INSTRUCTIONS



1

Wipe with the cleaning wipe


Wipe the screen clean with the cleaning wipe to remove fingerprints and oil.



2

Dry with the microfibre cloth


Wipe away any water stains or moisture with the microfibre cloth. The screen must be completely dry.



3

Remove the dust

Use the dust absorber to lift any remaining dust or lint off the screen.



4

Peel off the protective film


Peel the protective film from the adhesive side. Hold the protector by the edges and do not touch the adhesive.



5

Align and install

Align the protector to the edge of the screen, making sure it does not cover the microphone, then lower it slowly so it settles evenly.



6

Smooth out the air bubbles

Use the smoothing squeegee to push air bubbles from the centre out to the edges.

WARNINGS

- Do not fit the protector while driving. Fit it with the vehicle parked.
- Do not use heat or harsh chemicals on the screen or protector. Use only the supplied cleaning wipe.
- Clean the protector with the supplied microfibre cloth only. Rough cloths can mark the anti-glare surface.
- Do not press hard on the screen or use sharp tools. They can damage the screen or the protector.
- Do not touch the adhesive side. Fingerprints and dust will leave marks under the protector.
- If dust is trapped under the protector, lift it gently and remove the dust. Do not reuse a protector that is creased or has lost its grip.
- Check that touch response and any reversing camera or other on-screen functions work normally after fitting.